

A09 Typ 324-50 Kurzkegelflansch für ISO 702-1 (DIN 55026), beidseitig fertig bearbeitet (ohne Befestigungsschrauben)

Id.-Nr.	Ø A mm	Kegel	B mm	C mm	D mm	E mm	F mm	G	H mm	I	J mm
176804	125	3	17	102	53.975	51.2	70,6	3xø10,5	95	3x M8	108
176805	125	4	17	117	63.513	60.7	82,6	3x ø11	95	3x M8	108
176806	125	5	17	146	82.563	79.4	104,8	3x ø11	95	3x M8	108
176807	160	4	22	117	63.513	60.7	82,6	3x ø11	125	3x M10	140
176808	160	5	22.5	146	82.563	79.4	104,8	4x ø11	125	3x M10	140
176809	200	4	22.5	117	63.513	60.7	82,6	3x ø11	160	3x M10	176
176810	200	5	22.5	146	82.563	79.4	104,8	3x ø11	160	3x M10	176
176811	200	6	21.5	181	106.375	103	133,4	4x ø14	160	3x M10	176
176812	200	8	27	210	139.719	136	171,4	3x ø18	160	3x M10	176
176813	250	5	21	146	82.563	79.4	104,8	4x ø11	200	3x M12	224
176814	250	6	26	181	106.375	103	133,4	4x ø14	200	3x M12	224
176815	250	8	26	225	139.719	136	171,4	4x ø18	200	3x M12	224
176816	315	6	31.5	181	106.375	103	133,4	4x ø14	260	3x M12	286
176817	315	8	31	225	139.719	136	171,4	4x ø18	260	3x M12	286
176818	315	11	31	298	196.869	192.7	235	6x ø22	260	3x M12	286
176819	400	6	32.5	181	106.375	103	133,4	4x ø14	330	3x M16	362
176820	400	8	32	225	139.719	136	171,4	4x ø18	330	3x M16	362
176821	400	11	32.5	298	196.869	192.7	235	6x ø22	330	3x M16	362
176822	400	15	36	380	285.775	281.2	330,2	6x ø26	330	3x M16	362
176823	500	8	36	225	139.719	136	171,4	4x ø18	420	6x M16	458
176824	500	11	36	298	196.869	192.7	235	6x ø22	420	6x M16	458
176825	500	15	36	380	285.775	281.2	330,2	6x ø26	420	6x M16	458
176826	630	11	39	298	196.869	192.7	235	6x ø22	545	6x M16	586
176827	630	15	39	403	285.775	281.2	330,2	6x ø26	545	6x M16	586
159883	630	20	42	520	412.775	407.5	463,6	6x ø26	545	6x M16	586

